



## SMART EMBEDDED DISPLAY - 4.3-INCH IPS TFT LCD 480\*272 WITH CAPACITIVE TOUCH - ETEMB043013XDHAL

### Features:

- 16:9 4.3-inch 480\*272 resolution IPS TFT display module
- 16.7M colors
- Brightness: 650 nits with capacitive touch screen
- Industrial Interface: USB, RS485, RS232, CAN, I2C, SPI, GPIO
- 7-36VDC Power supply range.
- Super Wide View: 80/80/80/80(L/R/U/D)
- The capacitive touch panel can be flexibly customized with features such as water rejection, glove support, etc.
- Arm M7 based MCU, external SDRAM and flash (up to 128 MB)

[Print](#)

### Software

RTOS, GUI Development Software, and Initialization tool

FreeRTOS, TouchGFX, and CubeMX

### Board Support Package

TouchGFX's tpa file support  
Bootloader and flash-loader files

### IDE

GCC, CubeIDE, IAR, and MDK-ARM

### Overall

#### Size

4.3 inch

#### Outline Dimensions

130.04(W) x 88.86(H) x 13.1(D)(max) mm

Bonding Technology	Air Bonding
Display	
Color	16.7M
Panel Type	IPS-TFT LCD, Transmissive, Normally Black
Viewing Angle	Super Wide View, 80/80/80/80 (L/R/U/D)
Active Area (A.A.)	95.04(W) x 53.856(H) mm
Resolution	480RGB x 272
Brightness	650 nits
Viewing Area	96.04(W) x 54.86(H) mm
Active Area	95.04(W) x 53.865(H) mm
Dot Size	0.066(W) x 0.198(H) mm
Pixel Size	0.198(W) x 0.198(H) mm
Touch	
Type	Capacitive Touch Panel (CTP)
IC:	ILITEK ILI2511
Structure	2 mm chemically strengthened cover glass
Power Consumption	
Voltage	7~36 V
	7 V: 280 mA
Current	12 V: 170 mA
	36 V: 65 mA
Embedded	
MCU	STM32F750
Internal SRAM	320KB
External SDRAM	16MB
Internal Flash	64KB
External Flash	32MB
Interface	
USB	Full Speed
CAN	CAN 2.0
UART	RS232 and RS485
SPI	Support 3-wire and 4-wire
I2C	Yes
GPIO	6 pins
Programming	SWD interface (ST-link)
Environment	
Operating Temperature	-20~70 °C
Storage Temperature	-30~80 °C

Vibration

Operating: 2.45 m/s<sup>2</sup> (0.25g)

Storage: 11.76 m/s<sup>2</sup> (1.2g)

Shock

Operating: 29.4 m/s<sup>2</sup> (3g)


Storage: 490 m/s<sup>2</sup> (50g)

Certification

CE Certification

**ETEMB043013XDHAL** | **480(RGB) x 272**

**DIMENSIONS**



[www.edtc.com](http://www.edtc.com)

Emerging Display Technologies Corp.

Copyright 2007

Browser not compatible.